

display of high quality can be produced and power consumption is small at the time of use. An information device having this display unit, such as a portable phone, is also provided. The display unit has a color light emitting means, a reflecting means of external light and a light polarizing state modulating means. The display unit has a driving method switching means for switching color light emitting display and reflection display by on/off control of the light emitting means and switching control of a driving method of a display element.

REMARKS

The specification has been amended to correct errors of a typographical and grammatical nature. Due to the large number of corrections thereto, applicants submit herewith a Substitute Specification, along with a marked-up copy of the original specification for the Examiner's convenience. Applicants submit that the substitute specification includes no new matter. Therefore, entry of the Substitute Specification is respectfully requested.

The abstract has been amended to correct errors of a grammatical nature and to provide an abstract in proper format. A copy of the marked up abstract is enclosed.

Entry of the preliminary amendments and examination of the application is respectfully requested.

To the extent necessary, applicant's petition for an extension of time under 37 CFR 1.136. Please charge any

shortage in the fees due in connection with the filing of this paper, including extension of time fees, to Deposit Account No. 01-2135 (503.39687X00) and please credit any excess fees to such deposit account.

Respectfully submitted,



Melvin Kraus
Registration No. 22,466
ANTONELLI, TERRY, STOUT & KRAUS, LLP

MK/DRA/cee
Attachments
(703) 312-6600

503.39687XCE
MK

1

SPECIFICATION

TITLE OF THE INVENTION

COLOR/BLACK-AND-WHITE SWITCHABLE PORTABLE TERMINAL
AND DISPLAY UNIT



TECHNICAL FIELD

The invention relates to a display unit and a device using
this display unit, such as a portable phone, a portable
10 information terminal, a home electric product, etc.

BACKGROUND [ART] OF THE INVENTION

With respect to a ^{for displaying colors} (coloring) technique in the display unit
of a portable information device, Japanese Patent Laid-Open
15 No. 213799/1998 discloses a technique relating to a reflection
type color display ^{produced by} (of) a color filter system having auxiliary
illumination. Japanese Patent Laid-Open No. 106328/1998
discloses a technique relating to a liquid crystal display unit
for both reflection and transmission using a reflecting layer
20 having a light polarizing state maintaining property.
Japanese Patent Laid-Open No. 19257/1993 discloses a technique
relating to a field sequential color system ^{operating} as a color display
system in which no color ^{filter} (filter) is required. Japanese Patent
Laid-Open No. 10529/2000 discloses a technique relating to a
25 liquid crystal color display driving method in which red, green

and blue liquid crystal element operating signals are synthesized and set to a monochromatic video signal on the basis of ^a consumed power restraining command signal, and power consumption is reduced by displaying only this monochromatic
5 image.

As mentioned above, high image quality, ^{color} [coloring] and low power consumption are required in a [recent] portable information device, but many problems, ^{which are} described below, exist in the ^{display} technique ^{employed by} [relating to] the conventional color portable
10 information device.

SUMMARY [DISCLOSURE] OF THE INVENTION

First, in the reflection type color display of a system using ^a [the] color filter, a problem exists in that ^{the display} [an] image is
15 dark and is not easily seen in comparison with the reflection type black-and-white display ^{due to} [by] the absorption of light ^{by} [of] the color ^{filter} [filter at] each time [of using] external light and [using] auxiliary illumination. It is necessary to construct one pixel ^{from} [by] three subpixels of red, green and blue (hereinafter
20 respectively called R, G and B) to perform the color display. Therefore, a problem also exists in that ^{three-times the} power in the image display is required [three times] at any time in comparison with ^a [the] black-and-white display. Further, since the same driving system is adopted at each ^{time} [of] a device ^{is in use} [using time] and ^{at} a standby
25 time (a transmission display time and a reflection display

time), the difference in consumed power is only ^{equal to the} [a] difference in consumed power of ^{the} [a] light source itself due to turning-on and turning-off of the light source. Therefore, room for improvement is also left ^{as far as} [in a] reduction in power consumption ^{is concerned}.

5 Further, when a half mirror, a semi-transmitting reflection plate or a partial transmitting reflection plate having a partial opening portion, etc. are used as an external light reflecting means, a trade-off ^{exists between} [relation is formed in] luminance at the transmission display time and luminance at the reflection display time. Therefore, ^{the} image quality of incomplete brightness is formed in any display quality.

Accordingly, when ^a [the] color display system using ^a [the] color filter is adopted, a problem exists in that ^{the} power consumption is large and a dark display image is formed in comparison with the black-and-white liquid crystal display unit at each of the reflection display time and the transmission display time (auxiliary light source using time).

In contrast to this, if ^a [the] field sequential color display system using no color filter is adopted, the problem of the above-mentioned color filter can be solved, and ^a high image quality can be obtained. However, in this case, the light source must be lighted at any time to display the image, and it is considered that room for improvement is yet left ^{as far as} [in the] reduction in power consumption ^{is concerned} in a device [characterized in] ^{which} [that this device] has plural ^{of operation} [using] modes at the so-called device

using time and the standby time (transmission display time and reflection display time).

Therefore, an object of the invention is to provide a display unit for reducing power consumption ^{which is} [and] able to ^{produce a} [perform],

5 [the] color display, or a portable information device having this display unit, such as a portable phone, etc.

In accordance with one embodiment [mode] of the invention, a display unit having a light source has a mode switching section for switching a displayed image mode, a light source
10 control section for controlling [an] operation of the light source in accordance with instructions from the mode switching section, an image signal processing section for processing an image signal in accordance with instructions from the mode switching section, and a liquid crystal cell for displaying
15 ^{an} [the] image in accordance with the image signal from the image signal processing section. Accordingly, it is possible to realize a bright display unit with reduced power consumption and high contrast in each of ^a light emitting display and ^a reflection display.

20 In one [concrete] embodiment [mode], the image signal processing section of a driving section has a digital-analog converter and a level shifter. When the mode switching section switches the display mode to a multi-gradation display mode, the image signal generating section generates the image signal
25 of analog multi-gradation by using the digital-analog

converter. When the mode switching section switches the display mode to a two-gradation display mode, the image signal generating section generates ^{an} ~~the~~ image signal of analog binary gradation by using the level shifter. Accordingly, the driving method can be switched by using such a construction so that optimum power can be selected at any time, and consumed power can be optimized, and power consumption can be reduced.

Further, in another ~~[concrete]~~ embodiment ~~[mode]~~, the display element has a liquid crystal cell having a pair of transparent substrates, a liquid crystal layer ^{located} ~~[nipped]~~ between the pair of transparent substrates, and an electrode group arranged ^{on} ~~[in]~~ at least one of the pair of transparent substrates; a light polarizing maintaining diffusion reflection plate arranged on one face ~~[side]~~ of the liquid crystal cell; a light guide body arranged between the liquid crystal cell and the light polarizing maintaining diffusion reflection plate such that the light source is arranged on a side face of the light guide body; and a light polarizing maintaining scattering layer arranged between the light guide body and the liquid crystal cell. Accordingly, it is possible to realize a display unit in which ^{the} light utilization efficiency is further increased, and the problem of a double image is also solved in addition to the effects in which power consumption is reduced and the display of high contrast can be performed in each of the light emitting display and the reflection display.

Further, in an example ^{taken from} [in] a separate viewpoint of the invention, the display element has a liquid crystal cell having a pair of substrates; a liquid crystal layer ^{disposed between} [nipped by] the pair of substrates; plural pixels formed by an electrode [kind] arranged ^{on} [in] at least one of the pair of substrates; and a light source arranged in accordance with each of the plural pixels and constructed by including a metallic electrode, an organic LED layer and a transparent electrode from a substrate side. Accordingly, an image is displayed by adjusting ^{the} luminance of the organic LED at a color light emitting display time, and adjusting ^{the} luminance of the liquid crystal at a reflection display time. Thus, bright image display with reduced power consumption and high contrast can be realized, and the display element can be entirely reduced in thickness.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic ^{diagram} [view] showing one embodiment [mode] of a display unit of the invention.

Fig. 2 is a ^{waveform timing diagram} [view] showing a difference in driving method between ^a field sequential color display and ^a black-and-white display.

Fig. 3 is a block diagram of a D/A converter switching means.

Fig. 4 is a block diagram of a gradation bit switching means.

Fig. 5 is a ^{diagram} (view) showing an example in which 1-bit image data are generated from n-bit image data.

^{Figs. 6(a) and 6(b) are block diagrams illustrating overall}
 (Fig. 6 is a view for explaining entire) signal processing in a portable information terminal.

5 ^{Figs. 7(a) to 7(c) are signal diagrams}
 (Fig. 7 is a view) showing the relation of a scanning period, a liquid crystal response period and a light source lighting ^{respectively} period.

^{Figs. 8(a) and 8(b) are diagrams}
 (Fig. 8 is a view) showing a change in the light emitting intensity of a light source with the passage of time.

10 ^{Figs. 9(a) and 9(b) are views}
 (Fig. 9 is a) cross-sectional (view) of a display unit in an embodiment 1 of the invention.

Fig. 10 is a cross-sectional view of a display unit in an embodiment 2 of the invention.

^{Figs. 11(a) and 11(b) are views}
 (Fig. 11 is a) cross-sectional (view) of a display unit in
 15 an embodiment 3 of the invention.

^{schematic circuit diagram}
 Fig. 12 is a (view) of the construction of a pixel circuit of the display unit in Fig. 11.

^{diagram}
 Fig. 13 is a cross-sectional (view) of a display element in an embodiment 4 of the invention.

20 ^{schematic circuit diagram}
 Fig. 14 is a (view) of the construction of a pixel circuit of the display element in Fig. 13.

^{plan}
 Fig. 15 is a layout (view) of the pixel circuit of the display element in the invention.

^{diagram}
 Fig. 16 is a cross-sectional (view) of a display unit in
 25 an embodiment 5 of the invention.

Fig. 17(a) and 17(b) are diagrams showing
 [Fig. 17 is a typical view of] the schematic appearance
 of a portable phone in an embodiment 6 of the invention.

showing
 Fig. 18 is a block diagram [of] a main construction of the
 portable phone.

diagram
 5 Fig. 19 is a [view] showing a processing flow of a markup
 language.

is a diagram which
 Fig. 20 shows an example of a description using the markup
 language.

is a diagram which
 10 Fig. 21 shows an example of a display mode selection
 screen in the portable phone.

is a diagram which
 Fig. 22 shows an example of electronic commercial
 transactions.

Fig. 23 is a block diagram of a processing operation of
 commands or tag information for commanding ^a color light emitting
 15 display.

diagram showing a
 Fig. 24 is a typical view of an external appearance of
 the portable information terminal.

BEST MODE FOR CARRYING OUT THE INVENTION

20 One embodiment [mode] of a display unit of the present
 invention will be explained *with reference to* [by using] Fig. 1. The display unit
 of Fig. 1 is mainly constructed *to include* [by including] a display element
 101 and a driving section 105 for operating the display element
 101.

25 The driving section 105 will first be explained.

The driving section 105 has a signal processing switching section 106, a light source control section 111, and signal processing sections 112, 113.

The signal processing switching section 106 performs
 5 switching control of a processing method of an image signal displayed in the display element 101 and on/off control of a color light emitting means 103 through a driving signal interface 107 at any time. The switching control of the image signal processing method for displaying the image signal in
 10 the display element 101 ^{refers to} [means] e.g., ^a switching control of color light emitting display and reflection display in ^{accordance with} (view of) a display state. ^{for} [In view of] ^{display data} processing ^{contents}, for example, one of the signal processing sections 112, 113 is selected, switched and controlled in the switching control of the image
 15 signal processing method. Each of the signal processing sections 112, 113 processes ^{an} (the) image signal inputted from the ^{outside} [exterior], and converts the inputted image signal to an image signal suitable for (the) display [state], or generates [this] ^a
 20 processing sections for ^{performing such operations} [making such a work] means that the driving section 105 has plural paths for processing the image signal. In a concrete example of the switching control of the signal processing method, there are switching control of a driving frequency, switching control of each case of using and
 25 ^{not using} [unusing] a digital/analog converter, switching control of the

number of operated pixels, switching control of a circuit block for supplying a clock, etc. The light source control section 111 is a circuit section for controlling ^(an) operation of the light source arranged in the display element 101, and ^(an) operation of the light source control section 111 is controlled by the signal processing switching section 106. Each of these sections will be explained in detail in a later embodiment.

The switching control of the signal processing method, i.e., selection switching of the signal processing section, can

be performed by adopting such a construction. This finally means that consumed power can be switched. Accordingly, it

is possible to supply power ^{in accordance with the} ~~(by an)~~ amount required at each of the color light emitting display time and the reflection display time. Therefore, display with high definition and

high quality can be performed at the color light emitting display time, and ^{the unnecessary use of} ~~(useless)~~ power can be reduced, ^{whereby the} ~~(and)~~ consumed power can be optimized, and power consumption can be greatly

reduced at the reflection display time. As a matter of course, power can be also reduced by turning-on and turning-off the color light emitting means 103.

The driving section 105 in the display unit has ^(the) plural signal processing sections 112, 113 and the signal processing switching section 106. Power consumption of the display unit is reduced by switching the plural signal processing sections

^{using} ~~(by)~~ this signal processing switching section 106 at any time.

This simultaneously means that one display element has plural display states. Accordingly, it is necessary to set the display element itself to be adapted to the plural display states. Therefore, the display element 101 ^{can be designed} (is) also (devised), ^{to be} (and) combined with the (above) driving circuit section 105 so that power consumption is further reduced and image quality is further improved. In the following embodiments, an explanation ^{will be given of the use of one} (is made by using the) signal processing switching section and (the) plural signal processing sections, but one signal processing section and plural signal processing paths may be also arranged, or the signal processing switching section can be also arranged within the signal processing section when these actions are obtained. Various (kinds of) ^{different} modifications are included in a range ^{of possibilities, in which} (where the) plural signal processing paths can be arranged and (its) selection control can be performed.

The display element 101 will ^{next} (next) be explained.

The display element 101 is constructed by including a light polarizing state modulating means 102, a ^{colored} (color) light emitting means 103 for emitting ^{colored} (color) light, and an external light reflecting means 104 for reflecting external light 109. The ^{colored} (color) light emitting display ^{refers to} (means) both a case in which an illuminating means ^{other than} (except) for (the) external light is arranged, and light emitted from this illuminating means is modulated by the light polarizing state modulating means and is displayed

as an image, and a case in which a light emitting element is included and formed in each pixel of the display element, and an image is displayed by adjusting^{the} light emission and luminance of each light emitting element. In the former case, for example,

5 there is a liquid crystal display element in which a backlight is set to the illuminating means and a liquid crystal element is used as a luminance adjusting means. In this case, the liquid crystal display element is the light polarizing state modulating means 102, and the backlight is the ^{colored} [color] light
10 emitting means 103. In the latter case, there is a display element using an organic LED (Light Emitting Diode) display element and an organic EL (also called Electroluminescence) display element. In this case, the liquid crystal display element also corresponds to the light polarizing state
15 modulating means 102, but the organic LED display element corresponds to the ^{colored} [color] light emitting means 103. These examples and effects peculiar to this construction will be explained in later embodiments.

One of^{the} common features of the display element 101 is that
20 the ^{colored} [color] light emitting means 103 is arranged between the light polarizing state modulating means 102 and the external light reflecting means 104. Thus, the display element 101 of the invention can use a mirror of total reflection as the external
light reflecting means 104, ^{as} instead of a half mirror used in
25 the conventional display element. Accordingly, there is no

loss of (a) light (amount) due to the half mirror at each of the reflection display time and the ^{colored} (color) light emitting display time. Namely, no trade-off relation is formed in luminance between both ^{of} the displays. In a detailed explanation, almost

5 all of each of the external light 109 and the emitted light 108 is emitted to the exterior (upward in Fig. 1) of the display element 101 by the external light reflecting means 104, etc., and light can be efficiently utilized so that display of high contrast can be performed and ^{the} display quality can be improved.

10 Further, the light emitting means arranged on an upper face of the external light reflecting means has a function of the ^{colored} (color) light emitting display so that ^a bright ^{colored} (color) light emitting display can be ^{produced} performed without using a color filter. Furthermore, at the reflection display time, ^a black-and-white

15 display can be ^{produced} performed without using the ^{colored} (color) light emitting means 103 so that it is possible to adapt the display to each of the light emitting display, the reflection display and a different display method. This is particularly suitable for a device having the above driving circuit section, which can

20 reduce excessive power at the reflection display time ^(,) and is effective to reduce power consumption.

From the above description, power consumption of the driving section 105 is greatly reduced by switching of ^{the} signal processing (switching of the display states), and the display

25 element 101 is suitable for both the display states of the ^{colored} (color)

light emitting display and the reflection display, ^{so that it is possible to} [and can] ^{produce} ^{as well as} ^a display with high contrast and light, high image quality. Further, it is possible to provide a display unit with high image quality and reduced power consumption by

5 combining these constructions.

Detailed constructions of the display element 101 and the driving section 105 and effects peculiar to these constructions, etc. will be described in detail in the following embodiments.

10 The same reference numerals used in each figure designate the same or corresponding objects.

(Embodiment 1)

One embodiment of the display unit in ^{accordance with} the invention will be sequentially explained ^{with reference to} [by using] Figs. 1 to 5.

15 In the display unit of this embodiment, ^a light emitting display is performed by field sequential driving of multi-gradation color, and reflection display is performed by frame driving of ^a black-and-white binary display. The field sequential driving of the multi-gradation color is performed

20 at a light emitting display time, ^{during which} since the light emitting display time is a time ^{is used} [of using] the display unit, in many cases, and it is ^{believed} [considered] ^{the} to improve convenience of a user requiring the display of a larger amount of information with high image quality. The frame driving of the black-and-white binary

25 display is performed at a reflection display time since the

reflection display time is a standby time of the display unit in many cases, and it is considered to reduce power consumption while a function property of the display unit is secured. Namely, this display unit can optimize^{the} consumed power and
 5 reduce power consumption by switching driving methods in consideration of a function (display ability, etc.) required for the user at each of the color light emitting display time and the reflection display time. In this specification, the frame driving is a driving method for changing the driving
 10 voltage of a liquid crystal^{for} every one frame period, and this term is used to discriminate this frame driving from field sequential driving having plural subframe periods within one frame period.

Points ^{concerning} [of the] reduction in power consumption in the driving circuit section 105 (see Fig. 1) will ^{next} [next] be explained.
 15

As mentioned above, the driving section 105 has the signal processing switching section 106, the light source control section 111, and the signal processing sections 112, 113. ^{accordance with} In the invention, the display element 101 is set to have
 20 a display section including a display control section (a so-called scanning side driving circuit section, a signal side driving circuit section, etc.) for controlling the operation of an active matrix on an active matrix substrate. Each of^{the} constructional elements of the driving section 105 may be
 25 arranged on the active matrix substrate of the display element

101, and may be also arranged outside the display element 101.

The driving section 105 is rigidly considered as a functional

set of the above constructional elements, ^{however there is limit to the} ~~and~~ no position ^{of} ~~in~~ a concrete arrangement of this driving section 105 is strictly

5 limited.

The signal processing switching section 106 reduces power consumption by selectively using signal processing corresponding to each of the color light emitting display and the reflection display at any time. Here, we have noticed the
10 difference between both the displays, i.e., the driving method and gradation to reduce power consumption, and the power consumption is reduced with respect to each point. This construction will ^{next} (next) be explained.

First, a first point is to switch the driving methods,
15 i.e., operating frequencies. The field sequential color display method is adopted in the light emitting display. Therefore, each subfield (at least three subframe periods in total) of at least the three primary colors RGB is required to perform the color light emitting display in one frame period.
20 In contrast to this, frame driving of the black-and-white display is adopted at the reflection display time so that it is not necessary to arrange the subfield required at the color display time. Accordingly, ^{the} operating frequency at the reflection display time is reduced in comparison with ^{the} operating
25 frequency at the color light emitting display time, and can

be set to at least one-third and less. As a result, ^{the amount of} [a] power consumption (amount) can be greatly reduced. In this case, it is sufficient to add a circuit construction (driving frequency control section) for switching frequencies of the driving
 5 section.

A second point is to reduce power consumption by a method (memory switching method) for switching gradation. As mentioned above, this is because convenience is improved by adopting ^a multi-gradation display at the color display time, and power consumption is reduced by adopting ^a binary display
 10 at the black-and-white display time. The power consumption can be reduced by setting the binary display ^{to that} of black-and-white from [the] color multi-gradation, since the use of a digital-analog converter of relatively large power
 15 consumption required to perform the multi-gradation display is avoided. In this case, it is also useful to reduce the power consumption by ^{bypassing} [detouring] a signal path (digital-analog converter) of large power consumption, and simultaneously stopping the supply of a clock to the digital-analog converter.
 20 In this case, it is also useful to use a construction for changing memories at the color light emitting display time and the reflection display time. In this embodiment, this construction is realized by providing a function for realizing a memory switching method in the signal processing switching
 25 portion 106. In this specification, this gradation switching

method includes switching of an image signal and conversion of bits of the image signal. This method will be also described later.

In a separate view of the second point, at a normal time,
 5 i.e., when the light emitting display is selected, the display of a high bit number (n -bits) is performed. In contrast to this, when the reflection display is selected by commands of a user, etc., an image signal for the reflection display suitable for low power consumption is separately regenerated,
 10 and the display of a low bit number (m -bits $n > m$) is performed so that the power consumption is reduced.

A technique for reducing the power consumption will next be explained, ^{next} together with a concrete example.

Fig. 2 is an explanatory view ^{which illustrates} about the reduction in power
 15 consumption using switching of operating frequencies at the above first point.

In each of upper and lower waveforms of Fig. 2, the axis of abscissa shows time, and the axis of ordinate shows a voltage value applied to a pixel electrode. The upper waveform shows
 20 a voltage waveform applied at the field sequential color driving time, and the lower waveform shows a voltage waveform applied at the black-and-white frame driving time.

In the application voltage waveform 141 of the field sequential color driving, one frame period 143 is constructed ^{includes}
 25 by three subframe periods 140. In each of these subframe

periods 140, the application voltage corresponding to each of the three primary colors RGB is applied to the pixel electrode.

Since the three primary colors RGB corresponding to the application voltage are switched in an order of RGB every

5 subframe period, an observer recognizes this switching as ^a color display. In this figure, one frame period [is constructed by ^{includes} the three subframe periods. Therefore, for example, when ^{the} frame frequency is set to 60 Hz, it is necessary to set ^{the} subframe frequency, i.e., operating frequency to 180 Hz.

10 In contrast to this, in the application voltage waveform 144 of the frame driving, no subframe period exists within one frame period 143. Accordingly, similar to the above case, no subframe period exists even when ^{the} frame frequency is set to 60 Hz. Therefore, the frame frequency of 60 Hz is set to ^{the} operating frequency as it is.

This display unit notices a difference in operating frequency at the above field sequential color driving time and the frame driving time, and switches the operating frequency at the frame driving time to one-third of the operating frequency at the field sequential color display time. Thus, power consumption can be reduced by the difference in operating frequency. This construction can be realized by ^{providing} [arranging] an operating frequency control section for switching the frequency of a dot clock for controlling a time interval of

20 data transfer to a pixel in accordance with a display mode

25

within e.g., the driving section, a control section of an entire device, etc. At the black-and-white frame display time, i.e., the reflection display time, the power consumption is also reduced by turning-off the light source.

5 In Fig. 2, ^{the} voltage polarity of the application voltage of the field sequential color driving is inverted with respect to a central electric potential ^{for} every one subframe period, but ^{it also} can be [also] inverted every one frame period. Further, the number of subframes constituting one frame is not limited to
10 three. This is because the ^{object} point is to reduce power consumption by the difference in frequency.

Fig. 3 is a view ^{which will be referred to} for explaining a method ^{of} reducing power consumption by setting the black-and-white display at ^a the reflection display time to ^{in accordance with} binary display ^(at) the above
15 second point, i.e., a method ^{of} reducing power consumption by switching use and ^{non-use} [unuse] of a circuit block of relatively large power consumption, such as a digital-analog converter, etc. In Fig. 2, the color multi-gradation display is performed by n-bit display, and the black-and-white display is performed
20 by two-gradation display of 1-bit display.

Fig. 3 is a view showing the driving section 105 within the display unit. The driving section 105 has a signal processing switching section 106 having a memory control section 240 and a signal control section 245, a first signal
25 processing section 112, and a second signal processing section

113.

The first signal processing circuit section 112 has an n-bit memory 241 and a digital/analog converter 243. The second signal processing circuit section 113 has a 1-bit memory 242 and a level shifter 244. The n-bit memory 241 and the 1-bit memory 242 are arranged independently^(,) and have a function for holding image signals for the color display and the black-and-white display.

The memory control section 240 ^{is} (are) connected to at least the D/A converter 243, the level shifter 244, the signal control section 245, the 1-bit memory 241 and the n-bit memory 242, and performs a control operation such as the writing^(operation) of an image signal, etc. by selecting one of the memories in accordance with a control signal. For example, the control signal includes instructions for controlling one of the color display and the black-and-white display, etc. In this embodiment, this image signal is a digital signal. An image signal of n-bits is transmitted in the color multi-gradation display, and an image signal of one bit is transmitted in the black-and-white display (for example, a control section of the entire device if it is a portable device, etc.). In this case, the switching operation may be performed by judging the number of bits of the image signal ^{using} [by] the memory control circuit section. In this case, it can be also constructed such that the image signal is also a control signal.

In the above description, the driving section 105 selects a display path according to the transmitted image signal and the control signal.

An operation and effects of the signal processing switching section 106 in Fig. 3 will ^{next} [next] be explained.

When the memory control section 240 selects the n-bit memory 241 ^{using} [by] the control signal transmitted from the ^{outside} [exterior], the image signal is stored ⁱⁿ [to] the n-bit memory 241 [] and is then converted to an analog signal by the D/A converter 243. An image is then displayed in the display element 101 through the signal control section 245 and the driving interface 107. In contrast to this, when the memory control section 240 selects the 1-bit memory 242, the image signal is stored ⁱⁿ [to] the 1-bit memory 242 [] and is then converted to a binary analog signal by the level shifter 244. An image is then displayed in the display element 101 through the signal control section 245 and the driving interface 107.

In this embodiment, a combination using both the image signals of the n-bit gradation and the 1-bit gradation is adopted as the image signal transmitted from the ^{outside} [exterior]. However, the image signal of only the n-bit gradation is also ^{possible} [considered]. In this case, a section (bit converting section) for converting n-bits to one bit is added to the memory control section 240 or the signal processing section 113. This bit converting circuit section may be also arranged before or after

[the image signal is inputted to] the memory control section. When the bit converting circuit section is arranged after the [image signal is inputted to the] memory control section, this bit converting circuit section may be arranged before the 1-bit
 5 memory. In contrast to this, when the bit converting circuit section is arranged before [the image signal is inputted to] the memory control section, the memory control section 240 has this function. A concrete example of the case of generating a signal from n-bits to one bit will be described later.

10 As mentioned above, it is possible to ^{bypass} ~~detour~~ the D/A converter 243 of large power consumption by using a construction in which both the n-bit gradation display and the 1-bit gradation display (binary display) are provided, ^{in which} and the D/A converter 243 and the level shifter 244 are selected.
 15 Namely, power consumption can be greatly reduced at the one-bit gradation display (binary display) time. This is particularly effective in a situation in which low power consumption is important at a standby time in a portable phone using the display unit.

20 In this embodiment, the n-bit multi-gradation color display is performed at the time of using the D/A converter, and the one-bit black-and-white display is performed by two gradations of one bit at the time of using the level shifter (as an) ^{for} example. However, the display unit ^{also} may be [also]
 25 constructed such that the color display at the time of using

the D/A converter can be performed by the multi-gradation of n-bits, and the display at the time of using the level shifter can be set to the color display (eight-color display) of 1-bit gradation in which the 1-bit memory is arranged ^{for} ~~(every)~~ each of the three primary colors. This construction is suitable for a case in which only character information is displayed in color in a portable phone using this display unit, etc. This construction is also effective to reduce power consumption.

Otherwise, the display unit ^{also} may be ~~(also)~~ constructed such that ~~(the)~~ black-and-white display is performed by ~~(the)~~ n-bit gradation. This has an effect of a reduction in power consumption when a natural image is displayed in gray scale. This construction can be realized by ^{providing} ~~(arranging)~~ a circuit portion for converting a color image signal to a black-and-white image signal. Concretely, each of color multi-gradation display, color 1-bit gradation display, black-and-white (monochromatic) multi-gradation display and black-and-white (monochromatic) 1-bit display can be performed by the construction ^{provided in accordance with} ~~(of)~~ the invention.

^{and} The arrangement ~~(construction)~~ of the entire circuit is not limited to ^{that shown in} Fig. 3, but a construction ^{as} ~~(shown in)~~ Fig. 4 ^{also} can be ~~(also)~~ used. This construction will ^{next} ~~(next)~~ be explained. The difference in construction between Figs. 3 and 4 is that the n-bit memory ^{also} 241 ~~(can be)~~ ~~(also)~~ used in the case of ~~(the)~~ 1-bit gradation display. In a concrete construction, the n-bit

memory 241 of one kind is adopted as a memory[,] and is arranged independently of the D/A converter 243 and the level shifter 244.

5 ^{the} (An) operation and effects of the display unit ^{shown} in Fig. 4 will be explained. A memory control section 246 stores a supplied image signal to a necessary area of the n-bit memory 241 in accordance with a control signal. The image signal supplied to the memory control section 246 in this example is set to a combination of an n-bit gradation signal and a 1-
10 bit gradation signal. When the n-bit gradation display is performed, the n-bit gradation signal is supplied to the D/A converter 243. In contrast to this, when the 1-bit gradation display is performed, the 1-bit gradation signal is supplied to the level shifter 244. The D/A converter 243 generates an
15 image signal of analog gradation, and the level shifter 244 generates an image signal of binary gradation. One of the image signals generated through the signal control section 245 is supplied to the display element 101. In view of ^{the} consumed power, it is desirable to construct the display unit such that a clock
20 is supplied to only one of the D/A converter 243 and the level shifter 245 ^{depending on whether} (in accordance with the) n-bit gradation display or ^{is to be performed} (the) 1-bit gradation display.

As mentioned above, it is also possible to use a construction in which the image signal inputted from the
25 exterior of the driving section 105 is set to n-bits at any

time, and a circuit section (bit converting section) for converting the image signal to one bit is arranged before the memory control section 246, and a construction in which the bit converting section is arranged between the memory control
 5 section and the level shifter. Fig. 5 shows one example of a memory allocating method when the above bit converting section performs [the] 1-bit gradation display by using an n-bit signal. In Fig. 5, a value surrounded by a heavy line [in a] ^{at the} position [of] (n-1) in ^{the data representing} memory for green (G) shows an image signal
 10 in the two-gradation display.

For example, only the memory for green among memories for the three primary colors RGB is used by this memory allocating method, and the display of two gradations can be performed by using the value of a most significant bit of this
 15 memory. When the ^{color} image signal is constructed [by color] ^{of} n-bits, an image signal of one bit for the monochromatic two-gradation display can be generated.

^{Fig. 6(a) and 6(b)} [Fig. 6 is a view] ^{show examples of} systematically [showing] an entire flow of signal processing in a portable information terminal by
 20 including the judgment of a display mode, the generation of an image signal and transmission processing.

The portable information terminal 260 of Fig. ^{6(a)} [6A] has at least a display mode judging section 250, a signal generating section 251, a signal processing switching section 106, at
 25 least an n-bit memory, a first signal processing section having

a digital-analog converter connected to the n-bit memory, at least a 1-bit memory, a second signal processing section having a level shifter connected to the 1-bit memory, and a display section 252 (corresponding to e.g., a liquid crystal cell 101) for displaying an image. It is ^{proposed} considered, as an example of concrete constructions of the signal generating section and the display mode judging section, that a CPU having a function of both the signal generating section and the display mode judging section is ^{provided} arranged, and the display mode judging section and the image signal generating section are arranged in software (a program for controlling the operation of a device) of the CPU. Otherwise, it is also ^{proposed in} considered as the above example that the display mode judging section and the image signal generating section are ^{provided} arranged as a system LSI including the CPU. It is further ^{proposed in} considered as the above example that the CPU is the signal generating section, and the circuit section [of a] ^{for} display mode judgment is separately ^{provided} arranged, etc.

In Fig. 6^(a), the first and second signal processing sections are ^{separately} arranged, but may be combined with each other as ^{single} a signal processing section, and two processing paths may be arranged within this signal processing section, as mentioned above. Further, a signal processing switching section ^{also} can be ^{(a) or Fig 6(b)} included in the signal switching section of Fig. 6. The ^{also} following construction can be ^{also} applied to the construction

shown in Fig. 4.

The display mode of Fig. 6^{(a) and Fig 6(b)} is set to have color multi-gradation (n-bit gradation) and monochromatic two gradations (1-bit gradation). However, the above low light emitting mode^{also} can be also added to this mode. A monochromatic signal may be set to gradation of n-bits. In this case, it is necessary to arrange a bit converting section before the level shifter or the 1-bit memory.

✓ A processing flow in Fig. 6^(a) will first^{first} be explained.
 10 First, the display mode judging section 250 judges the display mode (display state) in the display section^{in response to} by a button operation^{by} of a user and commands of a markup language, and sends judging commands to the image signal generating section.
 15 Thereafter, the image signal generating section generates an image signal corresponding to the display mode of the display section based on information transmitted from a wireless portion, etc., and a control signal for controlling an operation of the signal processing switching section, and transmits the generated signals to the signal processing
 20 switching means. Each of the generated signals is an n-bit signal for color in the case of the color multi-gradation, and is a 1-bit signal for monochromatic display in the case of the monochromatic two gradations. The signal processing switching section^{upon} receiving the image signal and the control
 — 25 signal, selectively switches a path of signal processing, i.e.,

one of the first and second signal processing sections. The above selected signal processing section performs processing for converting the image signal to an analog signal, etc. Thereafter, the display section 152 displays an image by receiving the image signal. Thus, the display mode of the image can be arbitrarily switched, and convenience can be improved and power consumption can be reduced.

Switching timing of the display mode judged by the display mode judging section is not limited to the user's operation and the markup language, but timing in application, etc. is also considered as mentioned above. The display mode judging section 250 transmits commands to the signal generating section, but ^{also} (it is also included that) the signal generating section recognizes a judgment of the display mode judging section, and ^{the} ~~no~~ information transmitting direction is ^{not} limited to one direction.

The signal generating section ^{produces} (makes) the image signal and the control signal, but information of the control signal can be included in the image signal as mentioned above. For example, an operation, such as a switching operation performed by recognizing the bit of an image, is ^{possible} (considered). An operation such as an operation for reconverting a bit made by the signal generating section in accordance with the display mode, etc. is performed in this case.

Further, it is ^{proposed} (considered) that switching instructions

are directly transmitted to the signal processing switching section while the display mode judging section transmits instructions to the signal generating section and an image signal corresponding to the display mode is generated. It is also ^{proposed} considered that the image signal is generated irrespective of the display mode, but the display mode judging section judges the display mode of the display section and directly transmits instructions to the signal processing switching circuit section. This construction is effective when [works of] the signal switching and the image signal generation are independently ^{performed} made.

Fig. ^{6(b)} 6B will ^{next} (next) be explained. The difference between Figs. ^{6(a)} 6A and ^{6(b)} 6B is that the driving section has the construction of Fig. 4, and the display mode judging section 250 directly transmits instructions to the signal switching section without transmitting instructions to the signal generating section. ^{by} A processing flow will ^{next} (next) be described.

First, the display mode judging section 250 judges the display mode (display state) in the display section ^{in response to} (by) the button operation of a user and commands of the markup language, and transmits judging commands to the signal processing switching section. The signal processing switching section temporarily stores a transmitted image signal to the n-bit memory, and then ^{it} transmits the image signal to ^a selected one of the first and second signal processing sections. In this

case, when the signal switching section selects ^{the} ~~a~~ level shifter side, it is sufficient to arrange a bit converting section and an image converting section for converting the image signal for color to an image signal for monochromatic display, and

5 ~~(no)~~ ^{the} arrangement order of the bit converting section and the image converting section is ^{not} limited. For example, this [concrete] processing is performed by the processing [construction] explained with reference to Fig. 5. The above selected signal processing section performs processing such as conversion from

10 the image signal to an analog signal, etc. Thereafter, the display section 152 displays an image based on the image signal. Thus, the image in an arbitrary display mode can be displayed even when the signal generating section generates ^{an} ~~(the)~~ image signal corresponding to the same display mode at any time.

15 Accordingly, convenience can be improved and power consumption can be reduced.

Further, the driving circuit section 105 in this display unit also controls the operation of a backlight as a light emitting means, and the power consumption is also reduced in

20 view of this backlight control. This display unit will next be explained ^{with reference to (a) to 7(c) Figs. 8(a) and 8(b)} ~~(by using)~~ Figs. 7₁ and 7₂.

^{Figs 7(a) to 7(c) show} [Fig. 7 shows] the relation of a scanning period, a liquid crystal response period and a light source lighting period in an arbitrary subframe at a field sequential color display time₁ ^{respectively}.

25 In ^{Figs 7(a) to 7(c)} [Fig. 7], the axis of abscissa shows time in each of waveforms.

In this figure, a display element having m -gate lines and n -signal lines in the display section is ^{presented} [explained] as a concrete example. In this specification, scanning lines, signal lines, and a scanning circuit section and a signal circuit section for controlling operations of these scanning and signal lines are set to be arranged within the display section, and an image is displayed in the display section through a signal transmitted by the driving interface 107.

Fig. ^{7(a)} 7A is a view showing timing of gate selection pulses from a first gate line to an m -th gate line ($k=1$ to m). In this figure, reference numeral 150 designates a gate selection pulse.

A waveform 151 of Fig. ^{7(b)} 7B is shown in accordance with a gate line of Fig. ^{7(a)} 7A. The respective waveforms show response waveforms of liquid crystal molecules in pixels corresponding to a k -th gate line ($k=1$ to m) and an n -th signal line (final line).

A waveform 152 of Fig. ^{7(c)} 7C is a waveform showing lighting timing of the light source, and the [axis of] ordinate shows light intensity. The lighting of the light source is controlled by a light source control section in the driving section. For example, an operation of the light source control section is controlled by the signal processing switching section receiving the control signal.

One subframe period is constructed by ^{includes} three periods of

a scanning period required to scan m-gate lines, a liquid crystal response period required to ^{produce} ~~make~~ a sufficient response of the liquid crystal, and a light source lighting period for lighting the light source. Luminance depends on the intensity of transmitted light and th ~~a~~ lighting time. Therefore, if the light intensity is the same, a brighter display state can be obtained as the light source lighting period becomes longer. However, the light source lighting period is determined by subtracting the scanning period and the liquid crystal response period from one subframe period.

The liquid crystal response period is set to prevent a deterioration in image quality due to luminance irregularities of a pixel. When no liquid crystal response period is set, light is immediately emitted from the light source after the scanning period. However, no response of the liquid crystal is yet stabilized in a lower portion (near $K = m$) of a display area. Therefore, no desirable luminance can be obtained even when light is transmitted through this lower portion. As a result, a deterioration in image quality is caused.

The scanning period is set since there is a time difference between a time point for selecting a first gate line and a time point for selecting an m-th gate line. When no scanning period is set, a luminance difference is caused by lighting the light source in the scanning period between upper and lower portions ($k=1$ and m) of the display area even when

^{the}
[a] response time of the liquid crystal is a negligible short time. Therefore, a deterioration in image quality is caused.

Accordingly, it is necessary to set the scanning period and the liquid crystal response period, and ^{to} light the light source after the liquid crystal of the m-th line makes a sufficient response.

^(a)
As shown in Fig. 7, the scanning period is about one-third of the subframe period. Therefore, it is also useful to further reduce power consumption by stopping the supply of a clock signal to a display driver between the liquid crystal response period and the light source lighting period.

^{Fig. 8(a) and 8(b) show}
[Fig. 8 shows] a change in light emitting intensity of the light source with the passage of time in each display mode.

^{8(a)}
Fig. [8A] shows a change in time of the light emitting intensity in the field sequential color display. ^{8(b)}
Fig. [8B] shows a change in time of the light emitting intensity in low light emitting display. ^{Fig. 8(a) and 8(b) illustrate}
[Fig. 8 proposes] a power consumption method in the low light emitting display.

^{8(a)}
Fig. [8A] shows an example in which the field sequential color display is performed. In Fig. ^{8(a)} [8A], the [axis of] abscissa shows time and the [axis of] ordinate shows luminance. When [the] field sequential color display is performed, one of the light sources of the three primary colors (RGB) is sequentially lighted at least one time in a pulse shape every subframe period
140 in one frame period 143. Accordingly, the permutation of

a monochromatic light pulse is formed within one frame period 143 in a time arrangement of the light pulses of the three primary colors. In this embodiment, the subframe periods of the three primary colors are arranged in an order of red, green and blue so that the light sources are also correspondingly sequentially lighted in the order of red, green and blue. The subframe order may be replaced and set to an order of red, blue and green, etc. In this case, the lighting order of the light sources is also correspondingly replaced. The number of subframe periods existing within one frame period ^{also} can be [also] changed.

Fig. ⁸⁽⁶⁾ (8B) shows a case in which the low light emitting display is performed. In this figure, the [axis of] abscissa shows time and the [axis of] ordinate shows luminance. In this specification, the low light emitting display shows a third display system ^{accordance with} in the invention, and ^{it} shows an intermediate display mode between a display method for performing [the] light emitting display by turning-on the light source [] and a display method for performing [the] reflection display by turning-off the light source. Namely, this display mode shows black-and-white or monochromatic display, and light emitting display, although ^{the} luminance is low. The light sources of the three primary colors are simultaneously lighted and are used as a white light source (W), and light (continuous light 163) continuous in time is used as light emitted from the light

source. The light intensity is set to be lower than that at the color display time to reduce^{the} power consumption.

This display mode can be easily realized by separately and independently ^{switching} [switching] on/off ^{of} [of] the light source and the driving method.

This display mode has advantages in that^{the} power consumption is reduced by reducing^a frequency to^{the} frequency corresponding to frame driving, and ^a power amount of the light source can be reduced by reducing the light source intensity.

Namely, the light emitting display of low power consumption can be performed in comparison with a case in which the field sequential color light emitting display is performed. This is particularly effective^{for} ^{over} [in] use [for] a long time in a dark place, and is effective to improve convenience as a portable device.

^{8(b)} Fig. [8B] shows an example of the black-and-white display in which all the red, green and blue colors are lighted. However, it is also possible to perform ^{the} [the] monochromatic display in which only two or one color among the red, green and blue colors is lighted. Control for increasing the light source intensity

under a light environment and decreasing the light source intensity under a dark room environment may be also used by arranging a sensor for monitoring the intensity of^{the} environmental light. Thus, it is possible to prevent a reduction in color purity caused by superposing^{the} luminance of external light on^{the} luminance of the light source under the light

environment. Further, power consumption can be reduced while a sufficient visual recognizing property is obtained under the dark room environment. Further, it is useful to arrange a temperature monitor and control frame frequency in accordance with temperature, and switch the color light emitting display to the reflection display. This is because ^{the} (a) liquid crystal response speed is reduced under an environment at a low temperature, such as a below-zero temperature, so that the possibility of a reduction in color reproducibility is caused.

10 Thus, the frame frequency can be set to be low under the low temperature environment so that an influence on image quality due to the reduction in liquid crystal response speed can be prevented. Further, it is particularly useful to suitably replace the sequential time order of subframes ^{for} every color, and

15 every frame under the low temperature environment. Thus, it is possible to prevent a color ^{imbalance} (unbalance) caused by ^a (the) reduction in liquid crystal response speed under ^a (the) low temperature environment. Otherwise, the display unit may be also constructed such that the color display is compulsorily

20 switched to the black-and-white or monochromatic display at a temperature equal to or lower than a constant temperature.

In the field sequential color driving used in this embodiment, the light source is lighted in a pulse shape so as to increase ^{the} display luminance so that it is necessary to

25 set ^{the} peak power to be very high. Therefore, it is useful to

arrange a precharge circuit for lighting the light source in a pulse shape by continuous power in a light source control section of the driving section 105. A charge pump operation is performed by an action of this precharge circuit, and it is possible to prevent a sudden load due to generation of the peak power from being applied to a storage battery. Thus, wearing of the storage battery is reduced, and ^{the life} (a) time of (using) a device can be lengthened.

Further, when a point light source such as an LED, etc. is used, an incident light ratio can be improved by forming a notch in an incident portion of light emitted from the LED in a light guide body. A widening angle of emitted light can be widened by forming a cylindrical lens on an emitting face of the LED, and uniformity of illumination can be improved. If the above light emission can be performed, a fluorescent tube of each of the three primary colors RGB, etc. ^{also} can be (also) used.

As explained above, ^{the unnecessary use of} (useless) power can be reduced at the reflection display time and power consumption can be greatly reduced by arranging the driving section 105, having the signal processing sections 112, 113, and the signal processing switching means 106 in the display unit.

The display element 101 in this embodiment will ^{not} (next) be explained.

As mentioned above, ^{the} one of features of this display unit

is that the driving section 105 having a switching means ^{operating in accordance with} [of]

the signal processing method is arranged to reduce power consumption. However, since plural display states are set by switching the signal processing section, it is necessary to

5 devise the display element 101 in accordance with each of the display states. Accordingly, the display element

corresponding to both the display states of the light emitting display and the reflection display and which can improve image quality will ^{next} [next] be explained.

10 ^{Fig. 9(a) and 9(b) are} [Fig. 9 is a] ^{views} cross-sectional [view] of the display element 101 in the display element of this embodiment. ^{9(a)} Fig. [9A] shows the display element 101 at the color light emitting display time, and ^{9(b)} Fig. [9B] shows the display element 101 at the reflection display time. →

15 The display element 101 [in Fig. 9] is constructed by including a liquid crystal cell 132 and a backlight 129. The liquid crystal cell 132 corresponds to the light polarizing state modulating means 102 in Fig. 1, and the backlight 129 corresponds to the color light emitting means 103 and the
20 external light reflecting means 104 in Fig. 1.

A structure of the liquid crystal cell 132 in Figs. ^{9(a)} [9A] ^{9(b)} and ^{9(b)} [9B] will ^{first} [first] be explained.

The liquid crystal cell 132 is constructed by including a first light polarizing plate 120, a transparent substrate
25 121 having ^a [an unillustrated] transparent electrode, etc., a

liquid crystal layer 122, an active matrix substrate 123 having an [unillustrated] active matrix for operating the liquid crystal layer, and a second light polarizing plate 124.

A twist nematic mode for setting a twist angle to 90
 5 degrees is adopted in the liquid crystal layer 122. An orientation film for orientating the liquid crystal is formed on liquid crystal layer contact sides of the transparent substrate 121 and the active matrix substrate 123, although this construction is omitted in Fig. 8. Further, ^{the} (a) cell gap ^{, which is} @ the
 10 distance between the transparent substrate 121 and the active matrix substrate 123, is set to 2 μm in consideration of high speed ^{response} (responsibility) of the liquid crystal. If the field sequential color display can be performed, another display mode can be also applied naturally. When the display element is
 15 used in a portable information terminal, there are many cases in which this display unit is seen from a lower side. Therefore, an angle of visual field is symmetrically set on left-hand and right-hand sides, and is set to be wide from the lower side, and is set to be narrow on an upper side so that convenience
 20 is usefully improved. These constructions can be adjusted by ^{the} (a) rubbing angle.

The active matrix substrate 123 has a display portion in which pixels are arranged in a matrix shape. A transistor as an active element is arranged in each pixel. In this display
 25 element, a transistor using amorphous silicon is used as one

example, but any one of amorphous silicon, polycrystal silicon and monocrystal silicon may be also used as a semiconductor material forming an active element such as a transistor, etc. When amorphous silicon and polycrystal silicon are used, a
 5 glass substrate is normally used. Accordingly, in this embodiment, the glass substrate is used as the active matrix substrate 123. As a ^{production of} (making) method of the active matrix substrate, there are a method for arranging the active element in an epitaxial growing layer of monocrystal silicon formed
 10 on the glass substrate, and a method in which an active matrix circuit structure formed on a monocrystal silicon substrate in advance is separated by a lift-off method and is stuck onto the glass substrate.

Next, the backlight 129 (corresponding to the ^{colored} color light
 15 emitting means 103 and the external light reflecting means 104 in Fig. 1) in Figs. ^{9(a)} (9A) and ^{9(b)} (9B) will (next) be explained. The backlight 129 in the embodiment 1 has both a function for guiding light from a white LED as a light source to the liquid crystal cell 132 by scattering this light, and a function as
 20 a reflection plate for reflecting external light 109 incident through the liquid crystal cell 132.

The backlight 129 sequentially has a light polarizing maintaining type scattering layer 125, a light guide body 126 and a light polarizing maintaining scattering reflection plate
 25 127 ^{on one} (from a) side of the liquid crystal cell 132. The backlight

129 is constructed by arranging a white LED 128 which can perform field sequential lighting of the three primary colors on a side face of the light guide body 126. The light polarizing maintaining scattering layer 125 has a function for scattering transmitted light, but approximately maintaining a light polarizing state before and after the transmission. The light polarizing maintaining scattering layer 125 may be basically constructed by a layer in which ^{the} light absorption in ^{the} ~~an~~ entire visible ray ^{range} ~~(area)~~ is very small, and ^{the} refractive index is slightly changed in an order approximately equal to or smaller than a wavelength of light on a layer face in a thickness direction, and has a distribution. (Concretely,) For example, it is possible to apply a film formed by dispersing particles of a material slightly different in refractive index from a medium into a polymer film and resin, a hologram made by using a photosensitive material to an ultraviolet ray, etc., a layer using a material formed by dispersing particulates of a material slightly different in refractive index from an adhesive into resin such as an adhesive, a prism sheet having a scattering property, etc. When the prism sheet is applied, the prism sheet can function as a reflection plate ^{for reflection} of external light. The light polarizing maintaining type scattering reflection plate 127 has a function for reflecting and scattering light, but approximately maintaining a light polarizing state before and after the reflection. In a

structure of the light polarizing maintaining type scattering reflection plate 127, for example, fine irregular faces are formed on the surface of a light guide body, and a high reflectivity metallic plate of aluminum, etc. is formed by ^{an} [the] evaporation method, [the] sputtering method, etc. It is useful ^{obtaining} in uniformity of luminance to provide a distribution on a face with respect to the above fine irregular shape, and it is particularly useful to make emitted light 108 from the light source arranged on a side face uniformly incident ^{onto} [to] the liquid crystal cell 132. As another [concrete] constructional example of the light polarizing maintaining scattering reflection plate 127, there is an ^{embodiment} [example] in which the light guide body 126 and the reflection plate are adhered to each other by an adhesive, and particles of resin, glass, etc. slightly different in refractive index from the adhesive are dispersed into the adhesive. Further, it is also ^{possible to provide} [considered that] a polymer type liquid crystal layer, ^{disposed} [lipped] between transparent electrodes ^{in which} [is applied], [and], a scattering state and a transmitting state are switched by electric control, and the scattering state is set at the color light emitting display time, and the transmitting state is set at the reflection display time. In this case, a reduction in color purity caused by superposing white external light can be prevented, and it is particularly effective ^{during} [to consider] use under a bright environment, such as outdoors, etc.

The above light polarizing maintaining scattering layer 125 and the light polarizing maintaining type scattering reflection plate 127 may be arranged as one portion of the light guide body, as mentioned above, and ^{it} may be also arranged as a layer separated from the light guide body. This is because the ^{objective} (point) in this arrangement is to maintain the light polarizing states of incident light and reflected light.

✓ When a point light source such as an LED, etc. is used, the light polarizing state is maintained in the light guide body itself, and it is further preferable to use a light guide body having a scattering property. In this case, an effect of making a locus of light inconspicuous is obtained. It is considered that a construction for providing the scattering property is similar to that of the light polarizing maintaining scattering layer 125. However, it is necessary to set the scattering property of the light guide body to be weaker than that of the light polarizing maintaining scattering layer so as to maintain a light guide property of the light guide body. For example, it is necessary to devise the light guide body such that the density of particles dispersed into the above resin is reduced, etc. In this ^{case} (meaning), the light guide body may be ^{considered to be} [called] a second light polarizing maintaining scattering layer. ^{and} In this case, the light scattering property can be provided by forming a groove on an entire lower face of this light guide body. Further, when this groove is formed in a

prismatic shape, the light guide body can function as a reflection plate^{for reflection} of external light.

Operations and effects of the display element in the embodiment 1 at the color light emitting display time and the reflection display time will ^{next} [next] be explained.

First, the display element at the color light emitting display time in Fig. ^{9(a)} [9A], will be explained.

An LED [128] of each of the red, green and blue colors provided in the white LED 128 as a light source is sequentially lighted in time, and emitted light 108 is incident^{on} [to] the light guide body 126. The incident emitted light 108 is scattered and reflected on the light polarizing maintaining type scattering reflection plate 127 and the light polarizing maintaining type scattering layer 125, and is uniformly irradiated to the entire liquid crystal cell 132. The display section in the liquid crystal cell 132 synchronizes image information^{on} every color with the emitted light 108 of each of the red, green and blue colors emitted from the above white LED 128, and displays an image in the field sequential system.

The emitted light 108 transmitted through the liquid crystal cell is shifted in time in each of the red, green and blue colors, and is emitted in monochromatic color. However, an observer recognizes this emitted light as a color image^{due to the} [by] afterimage effects of^{the} eyes. This state is represented as the color light emitting display. In the embodiment 1, a diffusion means and

a diffusion reflection means are arranged such that the light guide body 126 is nipped. Therefore, the emitted light 108 can be approximately uniformly incident ^{on} (to) the liquid crystal cell 132 at any time. Further, since no color filter is used,

5 high light utilization efficiency can be obtained.

The display element at the reflection display time in Fig. 9(b) ^{will} ~~(next)~~ ^{not} be explained. Since no display element in the embodiment 1 has a color filter, the black-and-white display is set at the reflection display time.

10 In the black-and-white display, no white LED 128 is lighted, and external light 109 is used as the light source. The external light 109 is sequentially transmitted through the liquid crystal cell 132 and the light polarizing maintaining scattering layer 125, and is reflected on the light polarizing

15 maintaining scattering reflection plate 127 arranged in the light guide body 126. The external light 109 is again transmitted through the light polarizing maintaining scattering layer 125, and is modulated in luminance by the liquid crystal cell 132. Thereafter, the external light 109

20 is recognized as image information ^{on} in observer's eyes.

In the embodiment 1, the light polarizing state is maintained by arranging the light polarizing maintaining scattering layer 125 and the light polarizing maintaining scattering reflection plate 127 to brightly hold the reflection

25 display. ^{This feature} ~~(These contents)~~ ^{will} ~~(next)~~ ^{not} be explained.

First, the external light 109 used as ^a(the) light source is transmitted through first and second light polarizing plates 120, 124 of the liquid crystal cell 132. In this case, the external light 109 is absorbed by the first light polarizing plate 120, modulated by a liquid crystal layer 233, and absorbed by the second light polarizing plate 124 so that the external light 109 attains a light polarizing state. The external light 109 in the light polarizing state is then diffused and reflected on the light polarizing maintaining scattering layer 125 and the light polarizing maintaining scattering reflection plate 127. The external light 109 is again incident ^{on}(to) the liquid crystal cell 132 so that image information is obtained. However, in a case in which no light polarizing state (in an axial direction of a second polarizer 124 through which the reflected light is easily transmitted) is maintained when the reflected light 110 is again incident ^{on}(to) the liquid crystal cell 132, a light polarizing component shifted from a light polarizing direction is ^{produced}caused. Therefore, this shifted light polarizing component is again absorbed by the second light polarizing plate 124 of the liquid crystal cell 132 so that brightness is lost by this absorption. Accordingly, it is necessary to maintain the light polarizing state of the external light 109 before and after the reflection and the diffusion within the backlight 129. Therefore, in this embodiment, the light polarizing maintaining scattering layer

125 and the light polarizing maintaining scattering reflection plate 127 are used. When a sufficient scattering state is obtained by the first and second light polarizing maintaining scattering layers, the light polarizing maintaining scattering reflection plate 127 may be also set as a mirror face.

Light is also scattered and reflected by arranging the light polarizing maintaining scattering layer 125 and the light polarizing maintaining scattering reflection plate 127 to reduce the problem of a double image caused by parallax, etc.

The problem of the double image, etc. will ^{first} (first) be explained.

In a conventional reflection type liquid crystal display (having a structure) in which a liquid crystal cell ^{having} (sticking) light polarizing plates ^{on} (onto its) both faces is ^{provided} (arranged) and a reflection plate is also arranged outside the liquid crystal cell, a white image (light image) is formed on a surface of the reflection plate, and a black image (dark image) is formed in the position of a first light polarizing plate 120 (stuck) ^{disposed} onto an observer's side ^{thereof}. Accordingly, when these images are observed in a slanting direction shifted from a substrate normal line of the liquid crystal display, ^a (the) display image is seen ^{in which} (such that) the (forming) positions of the white and black images are shifted (are floated upward). Accordingly, a problem exists in that a double image caused by parallax is

seen.

Further, in a case in which the external light 109 reaches the observer by passing ^{through} different pixels when the external light 109 is incident ^{on} (to) the liquid crystal display and after the external light 109 becomes reflected light 110, ^{the} brightness levels and luminance levels of the [passing] pixels at the incident and reflection times are averaged and recognized by the observer. Accordingly, when the white and black images are adjacent to each other, a pixel to be originally seen ^{as} white looks slightly dark, etc. Therefore, ^{a fuzzy appearance} [luminance fuzz] of the display image is recognized, and a deterioration in image quality is caused. This problem becomes ^{even more} [further] serious in ^a [the] liquid crystal display using a color filter. Namely, when the external light and the reflected light pass through color filters of different colors, the color filters absorb the different ^{colored} [color] lights in nature. Accordingly, ^{the} light can be hardly transmitted, and ^{the} brightness of the display image is greatly reduced together with the ^{fuzzy appearance} [luminance fuzz] of the display image.

20 These problems become notable as the thickness of ^{the} [a] glass substrate constituting the liquid crystal cell is increased, and the distance between the display element and the reflection plate is increased. Therefore, a deterioration in image quality is caused. Accordingly, it is necessary to reduce the
25 thickness of the glass substrate and the distance between the

display element and the reflection plate so as to prevent this deterioration in image quality.

^{with in mind}
 In this ^{provides} viewpoint, the invention ^{provides} has a structure in which the light emitting means is arranged in front of the reflection plate. Accordingly, ^{the} [a] problem of increasing the distance between the [forming] position (reflecting position of the external light) ^{where} [of] the white image, and the [forming] position ^{is formed} (the position of the light polarizing plate) ^{where} [of] the black image, ^{is formed} remains. However, this problem is solved ^{accordance with} in the invention by
 10 arranging the light polarizing maintaining type scattering layer 125 between the liquid crystal cell 132 and the light guide body 126 to make the image forming positions of the white and black images approach each other. In this embodiment 1, no color filter is arranged. Accordingly, the problem of light
 15 interruption due to the color filter is naturally solved, and the problems of the so-called double image and the ^{fuzzy appearance of the image} [luminance] ^{is formed} [fuzz] are also solved so that the deterioration in image quality is prevented. These operational effects will [next] be
 explained.

20 First, the external light 109 is transmitted through the first light polarizing plate 120 of the liquid crystal cell 132, the liquid crystal layer 122 and the second light polarizing plate 124. After light and dark image information is obtained, the external light 109 is transmitted through the
 25 light polarizing maintaining scattering layer 125, and is

reflected on the light polarizing maintaining scattering reflection plate 127. The external light 109 is again transmitted through the light polarizing maintaining scattering layer 125 so that the external light 109 is scattered plural times. This light again has an approximately uniform intensity distribution. This uniform~~ed~~ light is [once]^{first} transmitted through the liquid crystal cell 132, and an observer recognizes this light as an image. In this case, the black image is formed in the first light polarizing plate 120, and the white image is formed between the liquid crystal cell 132 and the light guide body 126, i.e., [in]^{at} a position of the light polarizing maintaining scattering layer 125. As a result, the distance between the white and black images can be shortened. Thus, the^{problems of} double image due to parallax and the^{fuzzy image} (luminance fuzz) due to the averaging of brightness can be^{solved} [dissolved], and a display element of high image quality can be obtained. The light polarizing maintaining scattering reflection plate 127^{operating} as a reflecting means^{need} [does] not necessarily have a scattering means to obtain the above effects of making the image forming distances approach each other. However, it is more desirable that the reflecting means also has [the]^A scattering means in consideration of a viewpoint in which [the]^A uniform property of emitted light of the backlight at the light emitting display time is obtained.

25 The problems of the double image due to parallax, the

^{fuzzy image}
 1 [luminance fuzz], the light interruption due to the color filter,
 etc. can be solved for the first time by using the construction, ^{provided}
 in the embodiment 1 ^{according to} (from) the above description, while, ^{the} light
 efficiency is increased. Accordingly, it is possible to
 5 obtain a display element in which both the ^{colored} [color] light emitting
 display and the reflection display with high image quality can
 be performed by one display element. Power consumption, ^{also} can
 be [also] reduced by only the driving circuit section 105.
 Therefore, when it is sufficient to obtain effects of only the
 10 driving circuit 105, for example, it is also possible to use
 a reflection type display element of a front light type as the
 display element 101 in addition to the display element 101 ⁱⁿ of
 the invention. In the present system, negativity and
 positivity of the image are not inverted at the color light
 15 emitting display time and the reflection display time.
 Therefore, ^{the} (no) contrast ratio is ^{not} easily reduced even when the
 external light is superposed on light from the white LED 128
 as a light source at the field sequential color display time.
 Image display easily visualized (having high tolerance) can
 20 be performed at any time under various environments of
 different brightness levels.

As mentioned above, if the driving circuit section 105
 and the display element 101 ^{of} [explained in] this embodiment are
 used, it is possible to realize a bright display unit in which, ^{the}
 25 power consumption is low [] and contrast is high in each of the

light emitting display and the reflection display.

(Embodiment 2)

An embodiment 2 of the display unit ^{according to} ~~(in)~~ the invention will ^{with reference to} ~~(next)~~ be explained ^(by using) Fig. 10.

5 The display unit of this embodiment is constructed such that the field sequential color display ^{also} can be ~~(also)~~ performed at the reflection display time. This display unit is characterized in that a second liquid crystal cell 133 is newly arranged on the liquid crystal cell 132 of the display unit
10 in the embodiment 1. In this embodiment, various voltages are superposed and applied to this second liquid crystal cell 133 and ^{the} (a) birefringence ~~(amount)~~ of this liquid crystal cell is changed so that ^{the} (a) transmission spectrum is arbitrarily adjusted and is utilized as a switchable color filter. In another
15 example of the switchable color filter, a tunable filter of COLORLINK Corporation, etc. ^{is} ~~(are)~~ also preferable.

Fig. 10 shows a state in which the second liquid crystal cell 133 functions as a red(R) color filter at the reflection display time. In this embodiment, the voltage applied to the
20 liquid crystal cell is changed by synchronizing these filter colors sequentially changed and the field sequential image display. The color display corresponding to each subframe is sequentially performed so that an image is displayed in color.

^{It} (A) light amount is reduced by this construction since the
25 color filter is used. However, since this construction is

combined with the display unit in the embodiment 1, it is possible to obtain ^adisplay in which the above effects are obtained, i.e., the double image caused by parallax and the ^{fuzzy image} luminance fuzz due to averaging of luminance are ^{eliminated} removed.

5 Since ^{the} (an) entire face has a single color, there is no case in which the colors of transmitting filters of the incident light and the reflected light are different from each other. Therefore, the above problem of light interruption of the color filter caused by parallax is not caused. Accordingly, it is possible to sufficiently perform bright color image display with high image quality in comparison with the display unit using the normal color filter.

It is considered as one of ^{the} optimum utilization modes of the display unit having the above effects that the above reflection type field sequential color display is performed at the reflection display time, and the bright field sequential color light emitting display described in the embodiment 1 is performed without using the switchable filter at the color light emitting display time. In this case, it is desirable to arrange a filter switching circuit section for switching ^{between} use and ^{non-use} (unuse) of the switchable color filter in the driving switching circuit section 106 in accordance with necessity. Concretely, there is a method in which an organic LED selection switch (light source selection switch) and a liquid crystal selection switch for selecting the second liquid crystal cell

133 are independently arranged, and the color light emitting display and the reflection display are switched in accordance with ^{the} necessity of a user or device control software. The color filter can be also unused and the above reflection black-and-white mode can be also used at the reflection time in accordance with necessity of the user, etc.

It is possible to realize ^a bright image display with reduced power consumption by using the above construction at each of the color light emitting display time and the reflection display time.

(Embodiment 3)

An embodiment 3 of the display unit in the invention will be explained ^{with reference to Figs 11(a) and 11(b), which are} by using Fig. 11. Fig. 11 is ^a cross-sectional ^{views} (view) of a display element of the embodiment 3. Fig. ^{11(a)} 11A shows the case of a color light emitting display mode, and Fig. ^{11(b)} 11B shows the case of a reflection display mode.

In the embodiment ³ 3, the display unit in each of Figs. ^{11(a)} 11A and ^{11(b)} 11B is constructed by including a light polarizing plate 120, a phase plate 170, a glass substrate 121 having a transparent electrode 171, a liquid crystal layer 122, a liquid crystal pixel electrode 172, an organic LED anode electrode 174, an organic LED layer 175, an organic LED cathode electrode 176, a transistor 179, a wiring layer 178 for making electric connection between transistors 179, between the transistor 179 and the liquid crystal pixel electrode 172, and between an

(non-illustrated)
 [unillustrated] another transistor and the organic LED cathode electrode 176, etc., insulating layers 173, 177 arranged between wires, an active matrix substrate 180 in which pixels constructed by the transistor 179, etc. are formed in a matrix shape, etc.

The transparent electrode 171, the liquid crystal pixel electrode 172 and the organic LED anode electrode 174 are formed by indium tin oxide (ITO). The liquid crystal layer 121 is a liquid crystal layer of twist nematic orientation. In the orientation of this liquid crystal layer, another mode^{also} can be [also] used if it is another liquid crystal display mode which can perform the reflection type display of a single light polarizing plate type. A polycarbonate film extended in a specific direction and having a birefringence property is used as the phase plate 170. A polyvinyl alcohol film, a polystyrene film, etc. are also suitable as another material of the polycarbonate film.

The relation of the display unit of the embodiment 3 shown in Fig. 11(a) and 11(b) to Fig. 11 and the display unit shown in Fig. 1 will be explained here. The liquid crystal layer 122 corresponds to the light polarizing state modulating means 102, and the organic LED layer 175 corresponds to the ^{colored} [color] light emitting means 103, and the organic LED cathode electrode 176 corresponds to the reflecting means 104.

^{Detail} [Detailed contents] of Figs. 11(a) and 11(b) will [next] be

explained.^{next}

Fig. (11A)^(a) shows a case in which (the) color light emitting display is performed in the display element. In the display element, the organic LED layer 175 is operated, and light 108 is emitted to the exterior of the display element. In the color display, the organic LED layer of one of the three primary colors RGB is formed in each subpixel, and the three subpixels of RGB are set as one pixel, and ^{the} luminance of each subpixel within each pixel is arbitrarily adjusted. In the embodiment 3, the reflection type display system of a single light polarizing type and a normally black mode for performing black display at a voltage, ^{non-}(un)application time are adopted. Accordingly, the phase plate 170 and the liquid crystal layer 122 can be entirely equivalently operated as a one-fourth wavelength plate at a lighting time of the organic LED 175. Namely, even when external light 109 is incident ^{on} (to) the display element, a light polarizing state of the incident light is modulated by the phase difference plate 170 and the liquid crystal layer 122 and is absorbed ^{by} (to) the light polarizing plate 140. Therefore, no reflected light is finally emitted to the exterior of the display element, and no external light is offset and superposed. Accordingly, it is possible to obtain an effect in which a deterioration in the contrast ratio of a color ^{colored} light emitting image is prevented.

Fig. (11B)^(b) shows the case of the reflection display mode,

and shows a state in which the liquid crystal layer 121 is operated, and the external light 109 is modulated in intensity and is simultaneously reflected, and an image is displayed by the reflected light 110. In this case, the organic LED cathode electrode 176 functions as a reflection plate.

In a use in which it is sufficient if necessary and sufficient contrast is obtained, an effect of an increase in numerical aperture, i.e., luminance is obtained by omitting ^{the} [a] black matrix. Further, in this case, it is unnecessary to align upper and lower substrates so that a panel is easily made and cost is reduced. On the other hand, in a use in which a deterioration in contrast is prevented, the black matrix can be naturally used. Further, the display unit can be usefully constructed such that ^{the} (a) cell gap can be set with high accuracy, and it is unnecessary to align the substrates with each other by using a spacer for controlling the thickness between the substrates as a column structure.

The display unit of the embodiment 3 respectively performs display by a luminance adjustment of the organic LED at the color light emitting display time, and a luminance adjustment of the liquid crystal at the reflection display time. Accordingly, power consumption can be reduced, and ^a bright image display can be realized. Further, a reflection electrode layer of the organic LED layer ^{also} can be (also) used as a reflection plate in the liquid crystal display element by arranging the

organic LED layer and the liquid crystal layer on the same substrate. Further, since a necessary element is formed between a pair of substrates, there is an advantage in that the display element can be entirely reduced in thickness.

5 Furthermore, since the ^{at which} ~~(forming)~~ position ^{is formed} ~~(of)~~ a black image (dark image), and the ^{at which} ~~(forming)~~ position ^{is formed} ~~(of)~~ a white image (light image) can be set to approach each other, there are also advantages in that the above problems ^{of} ~~(about)~~ the double image caused by parallax and the ^{fuzzy image} ~~(luminance fuzz)~~ due to averaging of luminance
10 can be removed. Further, since no color filter is ^{used} ~~(arranged)~~, no problem of light interruption of the color filter caused by parallax is ~~(naturally)~~ caused.

In a concrete example of switching of the display method, it is considered that an organic LED selection switch and a
15 liquid crystal selection switch are independently arranged, and the color light emitting display and the reflection display are switched in accordance with ^{the} ~~(necessity)~~ of a user, etc. This construction will ^{next} ~~(next)~~ be explained.

Fig. 12 is a view showing an equivalent circuit of a pixel
20 in the display element of the embodiment 3.

An area surrounded by a broken line shows one subpixel 202, and the actual display section is constructed such that
a plurality of ^{are} ~~(this)~~ subpixels 202 ^{to form} ~~(is)~~ arranged longitudinally and transversally by a predetermined desirable number ^{arrangement} ~~(in)~~ a matrix ~~(shape)~~.

25 Each pixel includes at least a first transistor 179, a

holding capacitor 196, a liquid crystal layer 122, an organic LED layer 175 and a second transistor 198. An organic LED selection switch 194 and a liquid crystal selection switch 201 are arranged outside the pixel.

5 The organic LED selection switch 194 is connected to an unillustrated electric current supply source, and the liquid crystal selection switch 201 is connected to a portion having a common electric potential. A drain and a gate of the first transistor 179 are respectively connected to a data line 191
10 and a scanning line 190. This transistor 179 sample-holds a signal V_d of the data line 191 by the timing of a selection pulse inputted from the scanning line 190 to the gate. Namely, this electric potential is written to the holding capacitor 196 arranged between the transistor 179 and common wiring 200.

15 When the organic LED selection switch 194 is turned on and the liquid crystal selection switch 201 is turned off, an operation of the second transistor 198 is controlled by the signal V_d , and an electric current is supplied to the organic LED layer 175 by the electric current supply line 193, and the
20 organic LED layer 175 emits light at ^aspecific intensity in accordance with an electric current value. The electric current value may be constantly set, and light emitting luminance may be also adjusted by time width.

 In this state, no voltage is applied to the liquid crystal
25 layer 122 so that no liquid crystal layer 122 is operated.

Namely, this state shows that the color light emitting display is performed by only the light emitting luminance of the organic LED layer. As mentioned above, since the liquid crystal layer 122 in this state functions as a one-fourth wavelength plate, the display unit can perform high image quality display of high contrast.

In contrast to this, when the organic LED selection switch 194 is turned off and the liquid crystal selection switch 201 is turned on, the liquid crystal layer 122 is operated by the signal Vd, and no organic LED layer 175 emits light, since the second transistor 198 is turned off. Namely, the reflection display is performed by reflection of the external light and the effect of luminance modulation of this external light using the liquid crystal layer.

Operations of the organic LED layer 175 and the liquid crystal layer 122 can be arbitrarily switched by using such a construction in accordance with necessity. Further, the color light emitting display and the reflection display using the operation of the liquid crystal layer can be easily switched by arranging the respective subpixels 202 of the three primary colors RGB in parallel with each other and independently operating the subpixels 202. When the reflection display may ^{is to} be set to the black-and-white display, it is sufficient to arrange only one liquid crystal pixel electrode 172 for operating the liquid crystal layer 122 in three subpixels, and

it is also sufficient to arrange only one first transistor 179 connected to this liquid crystal pixel electrode 172 in three subpixels. In this case, the number of pixels operated at the black-and-white reflection display time can be set to one-third in comparison with the color light emitting display so that power consumption can be greatly reduced.

(Embodiment 4)

A display element in an embodiment 4 will be explained with reference to (by using) Fig. 13.


10 The display element of the embodiment 4 is constructed by including a first light polarizing plate 120, a phase plate 170, a glass substrate 121, a liquid crystal layer 122, a liquid crystal pixel electrode 172, insulating layers 210, 211, an organic LED layer 175, an organic LED cathode electrode 176, 15 common wiring 200 common to both the liquid crystal layer 122 and the organic LED layer 175, an active matrix substrate 180 in which pixels constructed by a transistor, a wiring layer, etc. are formed in a matrix shape, although this shape is not illustrated, etc. A wiring layer and a transistor under the 20 organic LED cathode electrode 176 are omitted for brevity in Fig. 12.

The liquid crystal pixel electrode 172 and the common wiring 200 are formed by ITO. The liquid crystal layer 122 has an orientation film and is a liquid crystal layer of 25 homogeneous orientation, although this construction is not

illustrated. An organic LED layer for emitting any one of the three primary colors RGB is formed in each of the subpixels arranged in parallel with each other. At the light emitting display time, the color display can be performed by arbitrarily
 5 modulating luminance levels of the three subpixels of RGB.

The embodiment 4 is characterized in that the common wiring 200 is arranged between the organic LED layer and the liquid crystal layer 122. The common wiring required in each of the organic LED layer 175 and the liquid crystal layer 122
 10 can be ^{combined} [commonized] by this construction. Further, an in-plane switching system for operating the liquid crystal by an electric field component parallel to the substrate can be adopted as the liquid crystal display system. In this case, it is necessary to adjust a liquid crystal material and the
 15 thickness of the liquid crystal layer so as to obtain a preferable contrast ratio in ^a [the] display of the reflection type. Further, it is also necessary to arrange the phase plate 170 in accordance with necessity. In the embodiment 4, the phase plate 170 is a one-fourth wavelength plate, and the reflection
 20 display having preferable characteristics in angle of visual field can be obtained by adopting the in-plane switching system.

The circuit construction of a pixel section of the display element in the embodiment 4 will be explained ^{with reference to} [by using]
 25 Fig. 14.

An area surrounded by a broken line shows [a] one subpixel
202. 

Each subpixel is constructed by including at least a first transistor 179, a second transistor 198, a third
5 transistor 214, a fourth transistor 215, a holding capacitor 196, an organic LED layer 175 and a liquid crystal layer 122. An organic LED selection switch 194 and a liquid crystal selection line 212 are arranged outside the subpixel.

The organic LED selection switch 194 is connected to an
10 electric current supply source. Each of the first, second and third transistors is an NMOS (n-channel Metal Oxide Semiconductor), and the fourth transistor is a PMOS (p-channel MOS). A drain and a gate of the first transistor 179 are respectively connected to a data line 191 and a scanning line
15 190. Gates of the third and fourth transistors are respectively connected to the liquid crystal selection line 212.

A case in which the organic LED selection switch 194 is turned on and the liquid crystal selection line 212 is set to
20 be low in voltage, will be explained. First, a signal V_d of the data line 191 is sample-held by the timing of a selection pulse inputted to the gate of the first transistor 179 through the scanning line 190. Concretely, the signal V_d is written to the holding capacitor 196 arranged between the data line
25 191 and organic LED common wiring 216. An electric current

supplied from common wiring 200 is applied to the organic LED layer 175 by controlling an operation of the second transistor 198 by a voltage of the signal Vd written to the gate holding capacitor 196. Thus, the organic LED layer 175 emits light at specific intensity in accordance with this electric current value. The electric current value can be constantly set, and ^{also} light emitting luminance can be (also) adjusted by time width.

At this time, the third transistor is turned off, and no voltage Vd of the holding capacitor 196 is applied to the liquid crystal layer 122. However, since the fourth transistor 215 is turned on, both ends of the liquid crystal layer 122 are connected to the common wiring 200. Accordingly, the voltage applied to the liquid crystal layer 122 becomes 0 Vrms so that the liquid crystal layer 122 is not operated, and contributes to an improvement of contrast ratio as a one-fourth wavelength plate.

When the organic LED selection switch 194 is turned off and the liquid crystal selection line 213 is set to be high in voltage, the fourth transistor 215 is turned off and the third transistor 214 is turned on. Therefore, the liquid crystal layer 122 is operated by the signal voltage Vd written to the holding capacitor 213. At this time, since the second transistor 198 is turned off, no organic LED layer 175 emits light. Accordingly, (the) reflection display using the liquid crystal layer can be performed.

The display element using ^{provided} [the] in-plane switching can be [made] by the above construction, and operations of the organic LED layer 175 and the liquid crystal layer 122 can be arbitrarily switched in accordance with necessity. Further, the color light emitting display and the reflection display of the liquid crystal operation can be easily switched by independently adjusting ^{the} light emitting luminance levels of the respective subpixels of the three primary colors RGB arranged in parallel with each other.

10 Fig. 15 is a view showing one subpixel 202 in one example of the layout of a pixel structure in the embodiment 4.

A display section is constructed by longitudinally and transversally arranging subpixels 202 by a required number in parallel with each other. The construction of each subpixel
15 is similar to that in Fig. 14.

The holding capacitor 196 is formed by crossing a source electrode of the first transistor and the organic LED common wiring 216. The holding capacitor 213 is formed by crossing the liquid crystal pixel electrode 172 and the common wiring
20 200. In Fig. 15, the organic LED anode electrode 176 and each of the first to fourth transistors 179, 198, 214, 215 are not overlapped. However, ^{the} numerical aperture can be increased by overlapping the organic LED anode electrode 176 on the above transistors. The liquid crystal pixel electrode 172 can be
25 also overlapped on the above transistors.

(Embodiment 5)

Fig. 16 shows a cross-sectional view of a display element of an embodiment 5. The embodiment 5 is characterized in that common wiring 200 is arranged approximately on the entire face of a lower portion of the liquid crystal pixel electrode 172. A light emitting area of the organic LED layer 175 is formed approximately in an entire area of pixels by this construction so that ^ahigh numerical aperture can be realized, and ^{the}luminance can be increased.

10 (Embodiment 6)

^{Figs. 17(a) and 17(b) are} ^{views}
 [Fig. 17 is a] typical [view] of the external appearance of a portable phone having the display unit ^{according to} [as] an embodiment 7 of the invention.

^{17(a)}
 Fig. [17A] shows a state in which information is monochromatically displayed in the display element 101 at a so-called "standby time" such as a time at which the portable phone 200 waits for an operation, etc.

^{17(b)}
 Fig. [17B] shows a state displaying information in color in the display element 101 at a so-called "using time" such as a signal reaching time, etc. In this concrete example, a talking partner is displayed.

The portable phone 220 of the embodiment 6 is constructed by including an antenna 221, a speaker 222, a display element 101, a key 223 such as a ten-key ^{pad}, etc., a microphone 224 and a camera 227 in each of Figs. ^{17(a)} [17A] and ^{17(b)} [17B].

In a ^{used} [using] mode of the portable phone, it is general to display the remaining amount of ^{life of the} [a] storage battery by an icon 225 even at the standby time, and display time at any time. In the future, a function of the portable phone as a portable
 5 information terminal will be provided and, for example, a ^{of use} [using] form for displaying a schedule at any time can be also sufficiently considered.

However, in the display method at the so-called standby time, it is sufficient to perform character display and icon
 10 display to a necessary minimum limit. Therefore, it is sufficient to perform black-and-white display or monochromatic display, and ^{the} [a] time ratio at the standby time is generally larger than that at the using time. In consideration of such situations, a most important performance
 15 required at the standby time is to reduce power consumption. Accordingly, the display system at the standby time is suitably a reflection type display system.

Fig. 18 is a block diagram of a main construction of the portable phone 220 of the embodiment 6.

20 The portable phone 220 of the embodiment 6 ^{has} [is constructed] [by including] an antenna 221, a wireless section 230, a talking processing section 233, a voice processing section 232, a control section 231 of the entire device, a camera 227, a speaker 222, a microphone 224, a key 223 such as a ten-key ^{pad},
 25 etc., a display unit 100 using the invention, an unillustrated

storage battery, etc. The control section 231 of the entire device judges the display state of an image (e.g., color display, monochromatic display)⁽¹⁾ and generates an image signal or a control signal according to each display state, and ^{it} transmits this generated signal to a driving circuit section. In this specification, the judgment of the display state also includes an operation switched by timing.

As already described, the display unit 100 of the invention is constructed by including the driving circuit section 105 and the display element 101. The control section 231 of the entire device and the driving circuit section 105 can be partially or entirely overlapped with each other in a certain case in generation, conversion, transmission and reception of the image signal, control of ^{the} clock frequency, etc.

For example, there is also a case in which the driving section 105 is ^{included} ~~made~~ within the control section of the entire device.

The driving circuit section 105 in the display unit 100 of the embodiment 6 has a driving method switching circuit section for switching the color light emitting display and the reflection display. In a switching condition of the display state, there are at least two cases ^{including a} ~~constructed by a switching~~ ^{of switching} case, from the color light emitting display to the reflection display, and a ^{of switching} ~~switching~~ case, from the reflection display to the color light emitting display.

For example, there are the following timings ^{with} ~~as~~ switching

timing from the reflection display or the black-and-white reflection display to the color light emitting display. In^a main timing, there is a specific operation of a user such as the following (1a) to (1g), and timing such as (1h) to (1k) can be also set to^a switching timing. A judgment about the switching timing of the color light emitting display and the reflection display is made by one of the control section 231 and the display unit 100, or both the control section 231 and the display unit 100 in cooperation with each other.

- 10 (1a) When a specific key is pushed down.
- (1b) When a folding state is switched to an open state.
- (1c) When a slide type cover and a strap cover are set to an open state.
- (1d) When a display section is exposed (a terminal having a
- 15 structure in which the display section is closed at an unusing time).
- (1e) When a specific voice is sensed (a terminal having a voice recognizing function).
- (1f) When a specific area of a touch panel is pushed down (a
- 20 terminal having the touch panel).
- (1g) When a dial is operated (a terminal having rotation, pushing-down and the dial).
- (1h) When a signal arrives.
- (1i) When an infrared signal is received (a terminal having
- 25 an infrared interface such as IrDA, etc.)

(1j) When a color image is received at a data communication time.

(1k) When a time preset by a user and application has passed.

(1l) When talking is terminated.

5 Conversely, for example, there are the following timings
 in the
 (as) switching timing from the color light emitting display to
 the reflection display or the black-and-white reflection
 display.

(2a) When a specific key is pushed down.

10 (2b) When an open state is switched to a folding state.

(2c) When a slide type cover and a strap cover is closed.

(2d) When the remaining amount of a storage battery is equal
 to or smaller than a constant value.

15 (2e) When a specific voice is sensed (a terminal having a voice
 recognizing function).

(2f) When a specific area of a touch panel is pushed down (a
 terminal having the touch panel).

(2g) When a dial is operated (a terminal having rotation,
 pushing-down and the dial).

20 (2h) When talking is terminated.

(2i) When an infrared signal is received (a terminal having
 an infrared interface such as IrDA, etc.)

(2j) When image data ^{are} ~~(are)~~ constructed by only a character [^] (such
 as a text and an icon, etc.).

25 (2k) When a time preset by a user and application has passed.

(21) When talking is started.

(No)^{the} switching timing is ^{not} limited to only the timings described in the embodiment 6.

In another example of the above switching timing, control
5 of the portable phone utilizing a connection service to the Internet such as the World Wide Web (hereinafter called WWW) is also considered. This construction will ^{next} (next) be explained.

A WWW site is normally described by HTML (Hyper Text Markup Language) as one kind of a markup language in which tag
10 information describing the attribute of a text and an image in a sentence is buried into the sentence. Software normally called a browser is used to display this WWW site in the display unit of a terminal of a person getting access to the WWW site. This browser has a function for referring to the tag information
15 buried into the HTML, and displaying the text and the image in the sentence, etc. by a shaping arrangement. Processing of the HTML ^{represents a} (is) large ^{to} (in) burden (in) an arithmetic unit of a device in which low power consumption of the portable information terminal, etc. is important. Therefore, a new markup language
— 20 considering a reduction in burden, such as a Compact HTML released by W3 Consortium, an MML (Mobile Markup Language) released by SFC research consortium MOBIDY project of keio-Gijyuku University, etc. ^{has been} (is) developed. Practical use of these languages in the portable information terminal is
25 expected.

In any markup language, color information can be designated as the attribute of the text, the image, etc. Concretely, color at the display time can be designated to the browser by describing a color attribute in the tag information.

5 The browser can refer to the color attribute in the tag information in the sentence described by the markup language, and can suitably display a color of the text, the color of a background image, etc. Namely, the tag information originally describing the attribute of the text and the image, etc. in
 10 the sentence can be utilized as ^{any capable judging} [a judging] element of efficient control of consumed power.

A concrete processing flow will be explained by using Fig. 19. The operation of an information device such as a portable information terminal, a portable phone, etc. is
 15 controlled by basic software normally called an OS (operating system). It is necessary that commands are given to the OS through an API (Application Programming Interface) and the OS gives commands of mode switching to hardware so as to switch the color light emitting display mode and the reflection
 20 display mode, the black-and-white reflection display mode or the black-and-white display mode by the browser.

In a concrete example, several cases are considered, as in the following ^{cases} (a) to (c).

(3a) When steps 1 to 5 in Fig. 19 are performed by the browser.

25 (3b) When steps 1 to 5 in Fig. 19 are performed by the OS.

(3c) One portion of steps 1 to 5 in Fig. 19 is performed by the browser, and the other is partially performed by the OS.

Shield may be also formed such that only the OS can utilize the API for switching the color light emitting display mode and the reflection display mode, the black-and-white reflection display mode or the black-and-white display mode, and no user of the OS can use the API. Otherwise, it is also possible to use a construction in which the OS can manage hardware for switching the color display mode and the black-and-white display mode, but it is not necessary to prepare such hardware in the API. This construction corresponds to a case in which useless switching of hardware using software operated on the OS is prevented on an OS side.

Fig. 20 ^{illustration} [shows a description] ^{to be used} example of the [used] markup language.

Fig. 21 shows the display screen of a device having the display unit using the invention when this device has a function which is able to select several operating modes in accordance with ^{the} necessity of a user. For example, "1. clean" mode for performing the color light emitting display at any time at the ^{of use} [using] time, "2. durable (indoor)" mode for performing ^{the} [the] black-and-white or monochromatic color display of low luminance at the ^{of use} [using] time, and "3. durable (outdoor)" mode for allocating the reflection mode at any time even at the ^{of use} [using] time, can be set in the operating mode which can be selected by the user. The user selects one of ^{modes} [lists from] 1 to 3 by a

key operation. Consumed power of the device can be suitably managed by providing such a function in accordance with a request of the user. In other words, power consumption of an information device can be more effectively reduced and the
 5 information device can be easily used by controlling an operation of the display unit in accordance with ^{the use} ~~(a using form)~~ of the information device.

A designer can arbitrarily allocate the above function to each operating mode in accordance with necessity. Further,
 10 ^{the} ~~(no)~~ operating mode is ^{not} limited to the embodiments in kind, number, name, etc.

A service to electronically order goods and settle accounts, etc. ^{using an} ~~(by the)~~ information device such as a portable phone, etc. is spread at present. Fig. 22 shows an embodiment
 15 relative to ~~(the)~~ service utilizing ^a ~~(the)~~ portable phone, etc. ^{according to} ~~(using)~~ the invention. This service is formed from the relation between four persons ^{established} ~~(constructed)~~ by a goods sales service provider, a connection service provider, a settlement provider and a user of the portable terminal 220 in this embodiment.
 20 Arrows between ^{each of} ~~(respective)~~ two persons among the four persons show service flows in information, goods, money, etc. as an example. For example, the goods sales service provider provides a service, such as ~~(goods)~~ sales of books, etc., provision of various kinds of information desired by the user, etc. One
 25 example of a providing means of the goods sales service is a

goods sales service performed by a goods sales site opened on the Internet.

For example, the connection service provider is a portable phone company, ^{which} [and] connects an information terminal
 5 of the portable phone possessed by the user, etc. to another information terminal, and provides a connection service to the Internet, etc. The settlement service provider receives a request from the goods sales service provider, and provides a service for proxy-executing settlement of the user.

10 For example, the settlement service provider ^{maybe} [is] a credit company, a bank, etc. The contract of a settlement proxy service is made in advance between the settlement service provider and the user. The settlement service provider can directly ^{communicate details} [notify contents] of the proxy-executed settlement to
 15 the user, or can ^{communicate such information} [notify these contents] to the information terminal of the user through the connection service provider. Conversely, the user can connect the information terminal to the settlement service provider through the connection service provider, and can also confirm the settlement ^{information} [contents].

20 A service form flow will next be explained. The user connects the information terminal of the portable phone, etc. to the goods sales service provider through the connection service provider, and orders predetermined desirable goods after the user selects the predetermined desirable goods, or
 25 inputs ^{dis or hr} [its] name, etc. The goods sales service provider sends

the goods to the user in accordance with the order from the user, and also asks the settlement service provider to pay for the goods. The settlement service provider proxy-executes the settlement of the user in accordance with the request from the goods sales service provider. The settlement service provider
 5 *communicates details*
 [notifies contents] of the settlement to the user.

For example, in a process in which the user connects the information terminal to the goods sales service provider and orders goods and confirms the settlement, it is effective to
 10 prevent the generation of an error in *the* order caused by an error in operation of the user *such* that the scene of making a contract is emphasized by the color light emitting display so *that the user will* (as to) clearly recognize this scene [by the user].

In a concrete embodying method, there are several methods
 15 as in the following *examples* (a) to (d).

(a) The goods sales service provider buries commands or tag information for designating the color light emitting display into a code for performing specific screen display in advance, and transmits the commands or the tag information to the
 20 information terminal through the connection service provider. The information terminal performs the color light emitting display in accordance with the above received commands or tag information.

(b) The goods sales service provider buries commands or tag
 25 information for designating the color light emitting display

into a code for performing specific screen display in advance. The connection service provider transmits second commands for designating the color light emitting display to the information terminal in accordance with the above commands or tag information. The information terminal performs the color light emitting display by receiving the above second commands received from the connection service provider.

(c) The goods sales service provider transmits a specific code, and the connection service provider receiving this code sets a response to specific commands or tag information included in this code in advance. If this response is designation of the color light emitting display, the connection service provider transmits second commands for designating the color light emitting display to the information terminal. The information terminal performs the color light emitting display by receiving the above second commands from the connection service provider.

(d) A response to specific commands or tag information included in a code transmitted from the goods sales service provider through the connection service provider is set in advance in the information terminal. If this response is the color light emitting display, the color light emitting display is performed.

Fig. 23 typically shows the relation of the above ^{examples} (a) ^{represents} to (d). A white circle (○) (shows a) generation (operation) of

commands or tag information instructing the color light emitting display, and a black circle (●) ^{represents} [shows] a processing operation corresponding to the commands or the tag information instructing this light emitting display. The processing operation ^{represented} [meant] by the black circle ● in the connection service provider corresponds to the generating [operation] ○ of commands or tag information newly instructing the color light emitting display. The processing operation ^{represented} [meant] by the black circle ● in the information terminal means that the color light emitting display is performed in accordance with the received commands or tag information instructing the light emitting display.

Another means for judging the contents of an image signal will [next] be described with respect to timing for switching the color light emitting display and the reflection display. Here, a means for judging whether it is a color image or a black-and-white image will be explained. The following embodiments are considered as [the] means for judging whether it is a color image or a black-and-white image.

(a) A comparing means for comparing whether each color image signal of RGB is the same or not is ^{provided} [arranged]. If each color image signal of RGB is different, it is judged as a color image. In contrast to this, if each color image signal of RGB is the same, it is judged as a black-and-white image.

(b) A color/black-and-white control line is ^{provided} [arranged] in

addition to a transmission line of the image signal, and the color or black-and-white display is performed by referring to this control line on a display side.

(c) When the color image is transmitted, all transmission lines
 5 of each color image of RGB are used. In contrast to this, when the black-and-white image is transmitted, only a signal line of one color among the transmission lines of each color image signal of RGB is used, and a discriminating signal showing no superposition of the image signal is transmitted on signal
 10 lines of the other two colors, or these signal lines are set to be open. The color or black-and-white display is performed on the display side by referring to this transmission, etc.

When the image signal is a color image signal, the black-and-white display may be preferentially performed in
 15 consideration of low power consumption. In this case, it is necessary to convert the color image signal to a black-and-white image signal. The display unit of this embodiment and a device having this display unit have a means for converting the color image signal to the black-and-white image
 20 signal. The color light emitting display may be switched to the black-and-white reflection display by manual commands of a user, and may be also automatically switched when the battery ^{image level} [remaining amount] is equal to or smaller than a constant value, etc. The image signal of RGB is switched to the black-and-white
 25 image signal by synthesizing a luminance signal value of each

color image of RGB with a weight of 299:578:114. There is no particular problem when an approximate value is used as the weight of RGB from the restrictions of a gradation bit number, a circuit scale, etc.

5 (Embodiment 7)

Fig. 24 shows a typical view of the external appearance of a portable information terminal unit having a display unit in an embodiment 7 of the invention.

The portable information terminal 260 of the embodiment
10 7 includes at least a display element 101, a main switch 261, a cursor key 262, a color light emitting/reflection display change-over switch 263, an antenna 264, etc.

Fig. 24A is a view in which the ^{shows on the left a} display element 101 in the portable information terminal 260, ^{which} performs the reflection
15 display. Schedule management software is used as one example of a screen displayed by this display element 101. In contrast to this, Fig. 24B is a view in which the ^{shows on the right a} display element 101 in the portable information terminal 260, ^{which} performs the color light emitting display. The portable information terminal 260
20 is connected to the Internet through the antenna 264, and a state displaying information obtained from the World Wide Web site of a sightseeing spot is shown as one example of the screen displayed by the display element 101. The reflection display is preferably performed with respect to the confirmation of
25 a schedule, etc., reference to only character information, and

information often referred^{to} so as to reduce power consumption as much as possible. In contrast to this, when the World Wide Web site including many color images is displayed, etc., it is possible to obtain^a display characteristically rich in entertainment by performing [the] color light emitting display. The portable information terminal 260 of this embodiment has [the]^a color light emitting/reflection display change-over switch 263, and is also constructed such that a user can switch the color light emitting display and the reflection display [in]^{with a} predetermined desirable timing. As described in the embodiment 1 of the device, the portable information terminal 260 is also constructed such that the color light emitting display and the reflection display are automatically switched by control software and application of the device.

The device having the display unit of the invention is not limited to the above portable phone and the portable information terminal, but can be also applied to a device having a display for displaying certain information at any time, e.g., a home electric device. If the display device of the invention is applied to the display of [the]^a home electric device, for example, it is possible to use a method in which [the] reflection display low in power consumption is normally performed, and is switched to the color light emitting display, etc. at any time at a time of [using]^{use of} the electric device or by commands of control software. Accordingly,^{the} visual [recognizing]^{recognition} property

of information displayed by the device is improved, and, ^{the} convenience for the user can be greatly improved.

INDUSTRIAL APPLICABILITY

5 As explained above, in accordance with the display unit of the invention, switching of the driving method of the display element is controlled simultaneously when on/off control of the light emitting means is performed. Further, the color light emitting means is arranged between the reflecting means
10 of external light and the light polarizing state modulating means. Accordingly, a display unit with reduced power consumption and high image quality can be provided.

ABSTRACT OF THE DISCLOSURE

(The invention provides ^Aa display unit ^{has a}in which brightness
 equal to that in a conventional black-and-white reflection type
 [is obtained] and ^{the}power consumption is small at a standby time,
 5 and bright color display of high quality can be ^{produced}[performed] and
 power consumption is small at ^{the}a using time ^{of use.} and also provides
^{An}[an] information device having this display unit, such as a
 portable phone, [etc.] is also provided.

The display unit has a color light emitting means, a
 10 reflecting means of external light and a light polarizing state
 modulating means [and is characterized in that] The display unit
 has a driving method switching means for switching color light
 emitting display and reflection display by on/off control of
 the light emitting means and switching control of a driving
 15 method of a display element.